

Dikaflex

sealing cords

Dikaflex is a malleable, asbestos-free sealing cord from non-hardening materials of consistent quality and strength. **Dikaflex** sealing cords are supplied ready to use.

Application:

Dikaflex is used in the **moulding and core shop**, particularly in **steel-** and **iron-foundries** as well as in the **non-ferrous** metal casting. With **Dikaflex** sealing strips separating gaps of moulds and cores from all mould materials are sealed. Further applications are the sealing of chill mould and cover ladle in foundries and steel mills.

Properties:

Dikaflex does not harden. **Dikaflex** dried by the high temperature of the metal and the moulds, disintegrates completely and leaves no harmful residue in the sand.

Application:

Dikaflex sealing cord is placed according to the size of the separating gaps. A break-through of the liquid metal, and thus leakage of the mould or the penetration of the metal in the core-venting is prevented.

Packing:

diameter	carton contents	carton weight	carton / pallet
[mm]	[m]	[kg]	
4	604	14,5	32
4,5	499	15	32
5	414	16,5	32
6	307	15	32
7	394	30	24
8	312	26	24
9	249	26	24
10	211	27	24
12	158	28	24
14	108	30	24
16	83	28	24
18	67	31	24
20	53	30	24
24	36	30	24
30	22,4	27	24

The cords each have a length of 80 cm, other diameters available on request.

Storage:

Cool, but frost-free in original packaging for at least 1 year.

Important Note:

Since our sealing cords also contain natural raw materials, whose conditions always show slight deviations, we point out that the end product (diameter) might have a tolerance of +/- 3-5%.

The above information is correct to the best of our knowledge and careful consideration. We guarantee the faultless and consistent nature of our products, however, we are not liable for further processing results that usually arise beyond our control. Safety Data Sheets are available and can be requested from KBO.

Dikaflex / EN / 2508